

Rotelle con perno CR30-VBUU-IKO - CR30-VBUU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr30-vbuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR30-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
19.050 ($\frac{3}{4}$)				CR 30 VBUU	418	47.625 ($\frac{1}{2}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	7-16	22.225 ($\frac{7}{8}$)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
25.8106	44.450 ($\frac{1}{2}$)	11.112 ($\frac{1}{2}$)	0.794 ($\frac{1}{8}$)	4.792 ($\frac{3}{8}$)	3.969 ($\frac{1}{4}$)	7.938 ($\frac{1}{2}$)	1.588 ($\frac{1}{8}$)	32.543 ($\frac{1}{2}$)	100	35 300	55 600

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060464163
Diametro interno	19.05 mm
Diametro esterno	47.625 mm
Spessore	25.4 mm
Peso	418 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE