



Ralle regispinta GS240380-IKO - GS240380-IKO

<https://www.123cuscinetti.it/accessori/rondella/ralle-regispinta/gs240380-iko>



THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
240	AZ 24038052	26 500	AZK 24038020	9 440	WS 240380	GS 240380	8 530

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
240	380	52	240.15	378	20	16	4	266	363	362	267	977 000	5 910 000	1 000

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060467485
Diametro interno	240 mm
Diametro esterno	380 mm
Spessore	16 mm
Materiale	-
Peso	8530 g
Imballaggio	-
Standard	-

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE