

Teste a snodo SI DSI5-T-K-DURBAL - DSI5-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/dsi5-t-k-durbal>


DSI5-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
DSI 5 T/K			5	M 5	8	6,00	18	8,5	11

type	measurement (mm)		h	d1	load rating	weight
DSI / DSI5 T/K	l1 min	W		PT	C0 (N)	[kg]
DSI / DSI5 T/K	10	9	27	13	6,0	0,016

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489056
Diametro interno	5 mm
Diametro esterno	18 mm
Spessore	8 mm
Tipo	SI
Peso	16 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE