

Teste a snodo SI SI6-T-K-DURBAL - SI6-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si6-t-k-durbal>


SI6-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 6 T/K		6	M 6	9	6,75	20	10,0	13

type	measurement [mm]			h	d ₁	load rating C ₀ [N]	weight [kg]
	l ₁ min	W					
SI / SIL 6 T/K	12	11		30	13	7,7	0,022

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489100
Diametro interno	6 mm
Diametro interno	0.236" inch
Diametro esterno	20 mm
Diametro esterno	0.787" inch
Spessore	9 mm
Spessore	0.354" inch
Tipo	SI
Peso	22 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE