

Teste a snodo SI
SI8-T-K-DURBAL - SI8-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si8-t-k-durbal>

SI8-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄	
SI 8 T/K		8	M 8	12	9,00	24	12,5	16	

type	measurement [mm]			load rating C ₁₀ [N]	weight [g]
	l ₂ min	W	h		
SI / SIIL 8 T/K	16	14	36	12,9	0,047

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489148
Diametro interno	8 mm
Diametro esterno	24 mm
Spessore	12 mm
Tipo	SI
Peso	47 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE