

Teste a snodo SI SI10-T-K-DURBAL - SI10-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si10-t-k-durbal>


SI10-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated

sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread		left hand thread		measurement [mm]						
	d	G	B	C1	d2	d3	d4	h	W	l1	l2
SI 10 TIK	10	M 10	14	10,50	28	15,0	19				

type	measurement [mm]			load rating C ₀ [N]	weight [kg]
	l ₁ min	W	h		
SI / SIL 10 TIK	20	17	43	18,0	0,077

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489209
Diametro interno	10 mm
Diametro esterno	28 mm
Spessore	14 mm
Tipo	SI
Peso	77 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE