

Teste a snodo SI SI25-T-K-DURBAL - SI25-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si25-t-k-durbal>


SI25-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 25 T/K			25	M 24 x 2	31	22,00	60	33,5	42

type	measurement (mm)			d ₁	load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h			
SI / SI/L 25 T/K	42	36	94	15	85,0	0,720

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489612
Diametro interno	25 mm
Diametro esterno	60 mm
Spessore	31 mm
Tipo	SI
Peso	720 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE