

Teste a snodo SI
SI28-T-K-DURBAL - SI28-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si28-t-k-durbal>


SI28-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 28 TIK		28	M 27 x 2	35	24,00	66	37,0	46

type	measurement [mm]			load rating C ₀ [N]	weight [g]	
	l ₃ min	W	h			
SI / SI28 TIK	51	41	103	15	107,0	0,820

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489681
Diametro interno	28 mm
Diametro esterno	66 mm
Spessore	35 mm
Tipo	SI
Peso	820 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE