

Teste a snodo SI SI35-T-K-DURBAL - SI35-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si35-t-k-durbal>


SI35-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 35 TIK		35	M 36 x 2	43	28,00	81	46,0	58

type	measurement [mm]			load rating C ₅ [kN]	weight [kg]
	l ₁ min	W	h		
SI / SIL 35 TIK	56	50	125	16	1,600

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489773
Diametro interno	35 mm
Diametro esterno	81 mm
Spessore	43 mm
Tipo	SI
Peso	1600 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE