

## Teste a snodo SA DSAL5-T-K-DURBAL - DSAL5-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/dsal5-t-k-durbal>

### DSAL5-T-K



**male thread; maintenance free, according to DIN ISO 12240-4, series K**

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
DSAL 5 T/K		5	M 5	8	6,00	18	

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
DSA / DSAL 5 T/K	19		33	13	6,0	0,013

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489919
Diametro interno	5 mm
Diametro esterno	18 mm
Spessore	8 mm
Tipo	SA
Peso	13 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE