

Teste a snodo SA SA18-T-K-DURBAL - SA18-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/sa18-t-k-durbal>


SA18-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]				
	d	G	B	C ₁	d ₂
SA 18 T/K	18	M 18 x 1,5	23	16,50	44

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 18 T/K	41	22	72	15	47,5	0,280

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952490205
Diametro interno	18 mm
Diametro esterno	44 mm
Spessore	23 mm
Tipo	SA
Peso	280 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE