

Teste a snodo SA SAL25-T-K-DURBAL - SAL25-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/sal25-t-k-durbal>

SAL25-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

male thread: maintenance free, according to DIN ISO 12240-4, series K


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number		measurement [mm]		Tragzahlen		weight
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 25 T/K		25	M 24 x 2	31	22,00	60

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 25 T/K	55	30	94	15	85,0	0,640

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952490328
Diametro interno	25 mm
Diametro esterno	60 mm
Spessore	31 mm
Tipo	SA
Peso	640 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE