

Teste a snodo SA SSAL25-T-K-DURBAL - SSAL25-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/ssal25-t-k-durbal>

SSAL25-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	d	G	B	C1	d2
SSAL 25 T/K	25	M 24 x 2	31	22,00	60

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 25 T/K	55	30	94	15	85,0	0,640

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952490953
Diametro interno	25 mm
Diametro interno	0.984" inch
Diametro esterno	60 mm
Diametro esterno	2.362" inch
Spessore	31 mm
Spessore	1.22" inch
Tipo	SA
Peso	640 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE