

Teste a snodo SI DSSI5-T-K-DURBAL - DSSI5-T-K-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/dssi5-t-k-durbal>

DSSI5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	d	G	measurement [mm]	B	C1	d1	d2	d3	d4
DSSI 5 T/K	5	M 5	8	6,00	18	8,5	11		

type	l ₁ min	W	h	α	load rating C ₀ [kN]	weight [kg]
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491059
Diametro interno	5 mm
Diametro esterno	18 mm
Spessore	8 mm
Tipo	SI
Peso	16 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE