

Teste a snodo SI DSIL5-PK-DURBAL - DSIL5-PK-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/dsil5-pk-durbal>

DSIL5-PK



female thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface case plated

Sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | measurement (mm) | |
|-------------------|------------------|------------------|
| right hand thread | d | G |
| DSIL 5 PK | S M 5 | 8 6,00 19 9,0 11 |

| type | measurement (mm) | | | load rating | weight |
|-----------------|------------------|---|----|-------------|--------|
| | l_1 min | W | h | C_0 (kN) | (kg) |
| DSI / DSIL 5 PK | 10 | 9 | 27 | 6,00 | 0,018 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952491806 |
| Diametro interno | 5 mm |
| Diametro esterno | 19 mm |
| Spessore | 8 mm |
| Tipo | SI |
| Peso | 18 g |
| Il filo | Filetto sinistro |
| Lubrificazione | senza |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE