

Teste a snodo SI DSIL14-PK-DURBAL - DSIL14-PK-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/dsil14-pk-durbal>

DSIL14-PK



female thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface case plated

Sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	d	G	measurement (mm)			
right hand thread			B	C ₁	d ₂	d ₄
DSIL 14 PK	14	M 14	19	14,00	37	20,0

type	measurement (mm)			alpha	load rating	weight
	l ₁ min	W	h	[°]	C ₀ (kN)	(kg)
DSI / DSIL 14 PK	25	22	57	14	31,00	0,160

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492056
Diametro interno	14 mm
Diametro interno	0.551" inch
Diametro esterno	37 mm
Diametro esterno	1.457" inch
Spessore	19 mm
Spessore	0.748" inch
Tipo	SI
Peso	160 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE