

Teste a snodo SI SI14-PK-DURBAL - SI14-PK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si14-pk-durbal>

SI14-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.


End end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	d	G	measurement (mm)				
SI 14 PK	14	M 14	19	14,00	37	20,0	25

type	measurement (mm)				load rating C ₀ (kN)	weight (kg)
	l ₁ min	W	h	α [°]		
SI / SI14 PK	25	22	57	14	31,00	0,160

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492070
Diametro interno	14 mm
Diametro interno	0.551" inch
Diametro esterno	37 mm
Diametro esterno	1.457" inch
Spessore	19 mm
Spessore	0.748" inch
Tipo	SI
Peso	160 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE