

Teste a snodo SA DSAL6-BK-DURBAL - SAL6-BK-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/sal6-bk-durbal>

DSAL6-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated
sliding combination:
steel / bronze-PTFE composite
inner ring:
bearing steel hardened and ground
Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

order number	measurement [mm]		C ₁	d ₂
	d	G		
right hand thread	6	M 6	9	21
left hand thread				
DSAL 6 BK				

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₂ min	h			
DSA / DSAL 6 BK	22	36	11	7,65	0,020

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492360
Diametro interno	6 mm
Diametro esterno	21 mm
Spessore	9 mm
Tipo	SA
Peso	20 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE