

Teste a snodo SA SAL22-BK-DURBAL - SAL22-BK-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/sal22-bk-durbal>

SAL22-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:

surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]				
	right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 22 BK	22		M 22 x 1,5	28	20,0		55

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₂ min	h			
SA / SAL 22 BK	50	84	15	68,00	0,480

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492698
Diametro interno	22 mm
Diametro esterno	55 mm
Spessore	28 mm
Tipo	SA
Peso	480 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE