

## Teste a snodo SA GAL12-UK-DURBAL - GAL12-UK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/gal12-uk-durbal>


### GAL12-UK



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	g	measurement (mm)		
right hand thread	left hand thread	B	C <sub>1</sub>	d <sub>2</sub>	
GAL 12 UK	12	M 12	10	8,0	34

type	measurement (mm)		h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l, min	l <sub>1</sub> min				
GAR / GAL 12 UK	28	18	54	11	24,5	0,086

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492896
Diametro interno	12 mm
Diametro esterno	34 mm
Spessore	10 mm
Tipo	SA
Peso	86 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE