

Teste a snodo SA GAR15-UK-DURBAL - GAR15-UK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/gar15-uk-durbal>


GAR15-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C1	d2
GAR 15 UK	15	M 14	12	10,0	40

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	l, min	l ₂ min				
GAR / GAL 15 UK	34	20	63	8	36,0	0,140

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492933
Diametro interno	15 mm
Diametro interno	0.591" inch
Diametro esterno	40 mm
Diametro esterno	1.575" inch
Spessore	12 mm
Spessore	0.472" inch
Tipo	SA
Peso	140 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE