


Teste a snodo SA
GAR25-UK-2RS-DURBAL - GAR25-UK-2RS-DURBAL
<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/gar25-uk-2rs-durbal>

GAR25-UK-2RS

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter d ≥ size 35 with additional seal on both sides (e.g. DGEAR... UK-2RS) bore diameter d ≥ size 17 additional seal on both sides upon request.



FERROBAL

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	measurement (mm)	C ₁	d ₂
right hand thread					
left hand thread					
GAR 25 UK (-2RS)	25	M 24 x 2	20	17,0	64

type	l, min	measurement (mm)	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 25 UK-2RS	53	32	94	7	83,0	0,560

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493176
Diametro interno	25 mm
Diametro esterno	64 mm
Spessore	20 mm
Tipo	SA
Peso	560 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE