

## Snodi sferici GE GAR40-UK-2RS-DURBAL - GAR40-UK-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/gar40-uk-2rs-durbal>


### GAR40-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)					
right hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
left hand thread						
<b>GAR 40 UK-2RS</b>	40	M 39 x 3	28	23,0	92	

type	l <sub>1</sub> min	measurement [mm]	h	alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
GAR / GAL 40 UK-2RS	86	48	150	7	180,0	1,800

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060467652
Diametro interno	40 mm
Diametro esterno	92 mm
Spessore	28 mm
Tipo	GE
Peso	1800 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1
Standard	Nessuno standard

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE