

## Teste a snodo SI GIL6-UK-DURBAL - GIL6-UK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/gil6-uk-durbal>

### GIL6-UK



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number right hand thread	measurement [mm]						
	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIL 6 UK	6	M 6	6	4,4	21	10,0	13
type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]	
	t <sub>3</sub> min	h	W				
GIR / GIL 6 UK	11	30	11	13	8,2	0,021	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493589
Diametro interno	6 mm
Diametro esterno	21 mm
Spessore	6 mm
Tipo	SI
Peso	21 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE