

Teste a snodo SI GIR12-UK-DURBAL - GIR12-UK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/gir12-uk-durbal>

GIR12-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]						
GIR 12 UK	d	G	B	C ₁	C ₂	d ₂	d ₄
	12	M 12	10	8,0	34	17,5	22
type	measurement [mm]			load rating	weight		
	t ₃ min	h	W	C ₀ [kN]	[kg]		
GIR / GIR 12 UK	23	50	19	24,5	0,096		

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493695
Diametro interno	12 mm
Diametro interno	0.472" inch
Diametro esterno	34 mm
Diametro esterno	1.339" inch
Spessore	10 mm
Spessore	0.394" inch
Tipo	SI
Peso	96 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE