

Teste a snodo SI GIR20-UK-2RS-DURBAL - GIR20-UK-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/gir20-uk-2rs-durbal>

GIR20-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free



order number	measurement [mm]						
right hand thread	d	G	B	C ₁	C ₂	d ₂	d ₄
GIR 20 UK (-2RS)	20	M 20 x 1,5	16	13,0	53	27,5	35

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 20 UK	40	77	32	9	60,0	0,350

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493855
Diametro interno	20 mm
Diametro esterno	53 mm
Spessore	16 mm
Tipo	SI
Peso	350 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE