

## Teste a snodo SI GIR30-UK-DURBAL - GIR30-UK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/gir30-uk-durbal>

### GIR30-UK



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]						
GIR 30 UK	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
	30	M 30 x 2	22	19,0	73	40,0	50
type	measurement [mm]			load rating	weight		
GIR / GIR 30 UK	t <sub>3</sub> min	h	W	C <sub>0</sub> [kN]	[kg]		
	56	110	41	6	110,0	0,930	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494005
Diametro interno	30 mm
Diametro esterno	73 mm
Spessore	22 mm
Tipo	SI
Peso	930 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1
Standard	Nessuno standard

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE