

## Teste a snodo SI GIL30-UK-DURBAL - GIL30-UK-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/gil30-uk-durbal>

### GIL30-UK



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free



order number	measurement [mm]					
GIL 30 UK	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub> d <sub>4</sub>
	30	M 30 x 2	22	19,0	73	40,0 50

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494050
Diametro interno	30 mm
Diametro interno	1.181" inch
Diametro esterno	73 mm
Diametro esterno	2.874" inch
Spessore	22 mm
Spessore	0.866" inch
Tipo	SI
Peso	930 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1
Standard	Nessuno standard

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE