

Teste a snodo SI GIL50-UK-2RS-DURBAL - GIL50-UK-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/gil50-uk-2rs-durbal>

GIL50-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free



| order number | d | G | B | measurement [mm] | d ₂ | d ₃ | d ₄ |
|---------------|----|----------|----|------------------|----------------|----------------|----------------|
| GIL 50 UK-2RS | 50 | M 45 x 3 | 35 | 30,0 | 112 | 62,0 | 75 |

| type | measurement [mm] | | | α [°] | load rating C ₀ [kN] | weight [kg] |
|---------------------|--------------------|-----|----|-----------------|---------------------------------------|----------------|
| | l ₃ min | h | W | | | |
| GIR / GIL 50 UK-2RS | 68 | 160 | 65 | 6 | 290,0 | 3,500 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952494203 |
| Diametro interno | 50 mm |
| Diametro interno | 1.969" inch |
| Diametro esterno | 112 mm |
| Diametro esterno | 4.409" inch |
| Spessore | 35 mm |
| Spessore | 1.378" inch |
| Tipo | SI |
| Peso | 3500 g |
| Il filo | Filetto sinistro |
| Lubrificazione | senza |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE