

## Teste a snodo SA POS5-DURBAL - POS5-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pos5-durbal>

POS5



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



rod end body:  
surface zinc plated  
Sliding combination:  
steel / heavy duty bronze  
Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated  
Outer ring:  
heavy duty bronze with lubrication  
Lubrication:  
lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	G	M	S	B	C <sub>1</sub>	d <sub>1</sub>	
POS 5	5	M 5		8	6,00	16	

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
POS / POSL 5	20	33	13	5,7	0,013

### CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494364
Diametro interno	5 mm
Diametro interno	0.197" inch
Diametro esterno	16 mm
Diametro esterno	0.63" inch
Spessore	8 mm
Spessore	0.315" inch
Tipo	SA
Peso	13 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE