


Teste a snodo SA POSL5-DURBAL - POSL5-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/posl5-durbal>

POSL5 

Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread: maintenance free, according to DIN ISO 12240-4, series K


rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required



order number		measurement [mm]	
right hand thread	left hand thread	B	C1
POSL 5		8	6,00
		M 5	16

type	measurement [mm]		α [°]	load rating C0 [kN]	weight [kg]
	l1 min	h			
POS / POSL 5	20	33	13	5,7	0,013

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494371
Diametro interno	5 mm
Diametro interno	0.197" inch
Diametro esterno	16 mm
Diametro esterno	0.63" inch
Spessore	8 mm
Spessore	0.315" inch
Tipo	SA
Peso	13 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE