

## Teste a snodo SI PHSL8-DURBAL - PHSL8-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/phsl8-durbal>

### PHSL8



**Description:** DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

**female thread:** lubrication required, according to DIN ISO 12240-4, series K


**rod end body:** surface chromium plated

**sliding combination:** steel / heavy duty bronze

**inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**outer ring:** heavy duty bronze with lubrication

**Lubrication:** lubrication required



order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
PHSL 8			8	M 8	12	9,00	22	12,5	16

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>2</sub> min	W	h	α [°]		
PHS / PHSL 8	16	14	36	14	11,6	0,047

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494982
Diametro interno	8 mm
Diametro esterno	22 mm
Spessore	12 mm
Tipo	SI
Peso	77 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE