

## Teste a snodo SI SIZPL9-S-DURBAL - SIZPL9-S-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sizpl9-s-durbal>

### SIZPL9-S



**Description:** DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

**female thread:** lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches


**rod end body:** surface zinc plated

**Sliding combination:** steel / heavy duty bronze

**inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** heavy duty bronze with lubrication

**Lubrication:** lubrication required, with grease nipple



order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIZPL 9 S		9,53	3/8 - 24
			B
			C1
			d2
			d3
			d4

type	inches	measurement [mm]			alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
		l <sub>1</sub> min	W	h			
SIZP / SIZPL 9 S	3 / 8 "	23,80	14,27	41,28	9	10,0	0,061

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952495736
Diametro interno	9.53 mm
Diametro interno	3/8" inch
Diametro esterno	25.4 mm
Diametro esterno	1" inch
Spessore	12.7 mm
Spessore	1/2" inch
Tipo	SI
Peso	61 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE