

Teste a snodo SI SIZP12-S-DURBAL - SIZP12-S-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sizp12-s-durbal>

SIZP12-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches


rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIZP 12 S		12,70	1/2 - 20	15,88	12,70	33,32	18,67	22,23

type	inches	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W	h			
SIZP / SIZPL 12 S	1 / 2 "	30,15	19,05	53,98	9	19,0	0,133

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952495828
Diametro interno	12.7 mm
Diametro esterno	33.32 mm
Spessore	15.88 mm
Tipo	SI
Peso	133 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE