

## Teste a snodo SI SIZP19-S-DURBAL - SIZP19-S-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sizp19-s-durbal>

### SIZP19-S



**Description:** DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

**female thread:** lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches


**rod end body:** surface zinc plated

**Sliding combination:** steel / heavy duty bronze

**inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** heavy duty bronze with lubrication

**Lubrication:** lubrication required, with grease nipple



order number	right hand thread		left hand thread		measurement [mm]							
	d	G	B	C1	d2	d3	d4	W	h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SIZP 19 S	19,05	3/4 - 16	22,23	17,45	44,45	25,02	28,58					

type	inches	measurement [mm]		h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
		d <sub>1</sub> min	W				
SIZP / SIZPL 19 S	3 / 4 "	44,45	25,40	73,03	10	29,0	0,285

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952495910
Diametro interno	19.05 mm
Diametro esterno	44.45 mm
Spessore	22.23 mm
Tipo	SI
Peso	285 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE