

Teste a snodo SA SAZP4-S-DURBAL - DSAZP4-S-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/dsazp4-s-durbal>


SAZP4-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated
Sliding combination:
steel / heavy duty bronze
Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated
Outer ring:
heavy duty bronze with lubrication
Lubrication:
lubrication required, with grease nipple

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|---------|------|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SAZP 4 S | | 4,83 | 10 - 32 | 7,92 | 6,35 | 15,88 |

| type | inches | measurement [mm] | | load rating | weight |
|------------------|--------|--------------------|-------|---------------------|--------|
| | | l ₁ min | h | C ₀ [kN] | W [g] |
| SAZP / SAZPL 4 S | | 19,05 | 31,75 | 10 | 0,013 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952495989 |
| Diametro interno | 4.83 mm |
| Diametro esterno | 15.88 mm |
| Spessore | 7.92 mm |
| Tipo | SA |
| Peso | 13 g |
| Il filo | Filetto destro |
| Lubrificazione | senza |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE