

## Teste a snodo SA DSAZPL4-S-DURBAL - DSAZPL4-S-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/dsazpl4-s-durbal>


### DSAZPL4-S



male thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4:  
series R,  
measurement in  
inches



Description: DIN ISO rod end K series. Dimensions in  
inch. Sliding combination steel / heavy duty bronze.  
With grease nipple.



Rod end body:  
surface zinc plated  
Sliding combination:  
steel / heavy duty bronze  
Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated  
Outer ring:  
heavy duty bronze with lubrication  
Lubrication:  
lubrication required, with grease nipple

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
DSAZPL 4 S		4,83	10 - 32	7,92	6,35	15,88

type	inches	measurement [mm]		load rating	weight
		h <sub>1</sub> min	h	C <sub>0</sub> [kN]	W [g]
DSAZP / DSAZPL 4 S		19,05	31,75	10	0,013

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496009
Diametro interno	4.83 mm
Diametro esterno	15.88 mm
Spessore	7.92 mm
Tipo	SA
Peso	13 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE