

Teste a snodo SA DSAZPL9-S-DURBAL - DSAZPL9-S-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/dsazpl9-s-durbal>


DSAZPL9-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated
Sliding combination:
steel / heavy duty bronze
Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated
Outer ring:
heavy duty bronze with lubrication
Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]			
right hand thread	left hand thread	d	G		
DSAZPL 9 S		9,53	3/8 - 24		
			B		
			C1		
			d2		
type	inches	measurement [mm]		load rating	weight
		l ₁ min	h	C ₀ [kN]	W [g]
DSAZP / DSAZPL 9 S	3 / 8 "	31,75	49,23	9	10,0

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496092
Diametro interno	9.53 mm
Diametro esterno	25.4 mm
Spessore	12.7 mm
Tipo	SA
Peso	55 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE