

## Teste a snodo SA SAZPL25-S-DURBAL - SAZPL25-S-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/sazpl25-s-durbal>

### SAZPL25-S



male thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4:  
series R,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions in  
inch. Sliding combination steel / heavy duty bronze.  
With grease nipple.



123BEARING

Rod end body:  
surface zinc plated

Sliding combination:  
steel / heavy duty bronze

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
heavy duty bronze with lubrication

Lubrication:  
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SAZPL 25 S		25,40	34,93

type	inches	measurement [mm]		load rating C <sub>0</sub> [kN]	weight [kg]
		h [mm]	α [°]		
SAZP / SAZPL 25 S	1"	53,98	104,78	14	1,100

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496313
Diametro interno	25.4 mm
Diametro esterno	69.85 mm
Spessore	34.93 mm
Tipo	SA
Peso	1100 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE