

## Teste a snodo SA SAZJ12-DURBAL - DSAZJ12-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/dsazj12-durbal>

### SAZJ12



female thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size  $\geq 9$  with grease nipple can be mounted upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
rod end body pressed around inner ring

Lubrication:  
lubrication required



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAZJ 12		12,70	1/2 - 20	15,88	11,50	33,32

type	inches	measurement [mm]		alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
		l <sub>1</sub> min	h			
SAZJ / SAZJL 12	1 / 2 "	38,10	61,93	10,0	28,0	0,110

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496559
Diametro interno	12.7 mm
Diametro esterno	33.32 mm
Spessore	15.88 mm
Tipo	SA
Peso	110 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE