

Teste a snodo SI SIZJ4-DURBAL - SIZJ4-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sizj4-durbal>

SIZJ4



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required



order number	right hand thread	left hand thread	measurement [mm]					
	d	B	C ₁	d ₂	G	d ₃	d ₄	
SIZJ 4	4,83	7,92	5,94	15,88	10 - 32	7,54	10,31	

type	inches	h ₁ min	measurement [mm]		α	load rating	weight
			W	h	[°]	C ₀ [kN]	[g]
SIZJ / SIZJL 4		12,70	7,92	26,97	10,0	6,8	0,018

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496665
Diametro interno	4.83 mm
Diametro esterno	15.88 mm
Spessore	7.92 mm
Tipo	SI
Peso	18 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE