

Teste a snodo SI SIZJ9-DURBAL - DSIZJ9-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/dsizj9-durbal>

SIZJ9



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size: 9 with grease nipple can be mounted upon
request.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required



order number		measurement [mm]						
right hand thread	left hand thread	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJ 9		9,53	12,70	9,12	25,40	3/8 - 24	13,89	17,45

type	inches	l ₁ min	measurement [mm]		α	load rating	weight
			W	h	[°]	C ₀ [kN]	[kg]
SIZJ / SIZJL 9	3 / 8"	19,05	14,27	41,28	11,0	16,0	0,059

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496795
Diametro interno	9.53 mm
Diametro esterno	25.4 mm
Spessore	12.7 mm
Tipo	SI
Peso	59 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE