

Teste a snodo SI SIZJL19-DURBAL - SIZJL19-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sizj19-durbal>

SIZJL19



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJL 19	19,05	22,23	15,06	44,45	3/4 - 16	25,02	28,58

type	inches	h ₁ min	measurement [mm]	h	α	load rating	weight
			W		[°]	C ₀ [kN]	[kg]
SIZJ / SIZJL 19	3 / 4 *	34,93	25,40	73,03	12,0	44,0	0,295

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496948
Diametro interno	19.05 mm
Diametro esterno	44.45 mm
Spessore	22.23 mm
Tipo	SI
Peso	295 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE