


Snodi sferici GE SI12-E-DURBAL - SI12-E-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/si12-e-durbal>

SI12-E 

female thread;
lubrication
required,
according to
DIN ISO 12240-4;
serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 12 E	measurement [mm]		measurement [mm]				measurement [mm]			
	d	G	B	C ₁	d ₂	d ₃	d ₄	W	h	α
SI 12 E	12	M 12	10	8,0	34	17,5	22			

type	measurement [mm]		h	α	load rating C ₀ [kN]	weight [kg]
	l ₃ min	W				
SI / SII 12 E	23	19	50	11	24,5	0,096

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468000
Diametro interno	12 mm
Diametro esterno	34 mm
Spessore	10 mm
Tipo	GE
Peso	96 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE