

Teste a snodo SI SIL17-ES-DURBAL - SIL17-ES-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sil17-es-durbal>

SIL17-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
		d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 17 ES		17	M 16	14	11,0	46	24,0	30

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [g]
SI / SIL 17 ES	34	27	67	10	45,0	0,22

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497037
Diametro interno	17 mm
Diametro interno	0.669" inch
Diametro esterno	46 mm
Diametro esterno	1.811" inch
Spessore	14 mm
Spessore	0.551" inch
Tipo	SI
Peso	220 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE