

Teste a snodo SI

SIL25-ES-2RS-DURBAL - SIL25-ES-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sil25-es-2rs-durbal>

SIL25-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
d	G	B	C ₁	d ₂	d ₃	d ₄		
SIL 25 ES (-2RS)		25	M 24 x 2	20	17,0	64	33,5	42

type

type	l ₃ min	W	h	α [°]	load rating C ₀ (kN)	weight (kg)
SI / SIL 25 ES (-2RS)	48	36	94	7	83,0	0,64

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497143
Diametro interno	25 mm
Diametro esterno	64 mm
Spessore	20 mm
Tipo	SI
Peso	640 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE