

Teste a snodo SI
SIL25-ES-DURBAL - SIL25-ES-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sil25-es-durbal>

SIL25-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required



order number
right hand thread left hand thread
SIL 25 ES

measurement (mm)	
d	G
25	M 24 x 2

measurement (mm)	
B	C ₁
20	17,0

measurement (mm)	
d ₂	d ₃
64	33,5

measurement (mm)	
d ₄	d ₅
42	

type	l ₂ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SIL 25 ES	48	36	94	7	83,0	0,64

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497150
Diametro interno	25 mm
Diametro esterno	64 mm
Spessore	20 mm
Tipo	SI
Peso	640 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE