

Teste a snodo SI SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si25-es-2rs-durbal>

SI25-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.


rod end body:
surface zinc plated

Sliding combination:
steel / steel

inner ring:
bearing steel, hardened, ground and
phosphated

outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



order number	measurement [mm]	
	right hand thread	left hand thread
SI 25 ES (-2RS)	25	M 24 x 2

type	measurement [mm]				load rating C_0 [kN]	weight [kg]
	l_1 min	W	h	α [°]		
SI / SII 25 ES (-2RS)	48	36	94	7	83,0	0,64

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497198
Diametro interno	25 mm
Diametro interno	0.984" inch
Diametro esterno	64 mm
Diametro esterno	2.52" inch
Spessore	20 mm
Spessore	0.787" inch
Tipo	SI
Peso	640 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE