

## Teste a snodo SI SI30-ES-2RS-DURBAL - SI30-ES-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si30-es-2rs-durbal>

### SI30-ES-2RS



female thread;  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and  
phosphated

Outer ring:  
bearing steel, hardened, ground and  
phosphated

Lubrication:  
lubrication required



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 30 ES (-2RS)		30	M 30 x 2	22	19,0	73	40,0	50
type	l <sub>2</sub> min	measurement [mm]		h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]	
SI / S1L 30 ES (-2RS)	56	41	110	6		110,0	0,93	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497228
Diametro interno	30 mm
Diametro esterno	73 mm
Spessore	22 mm
Tipo	SI
Peso	930 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE