

Teste a snodo SI
SIL35-ES-DURBAL - SIL35-ES-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sil35-es-durbal>

SIL35-ES

female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E




Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required



order number
right hand thread left hand thread

SIL 35 ES

measurement (mm)	
d	G
35	M 36 x 3

measurement (mm)	
B	C1
25	21,0

measurement (mm)		
d2	d3	d4
82	47,0	58

measurement (mm)					
l2 min	W	h	alpha [°]	load rating C0 (kN)	weight (kg)
60	50	125	6	146,0	1,3

SI / SIL 35 ES

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497310
Diametro interno	35 mm
Diametro esterno	82 mm
Spessore	25 mm
Tipo	SI
Peso	1300 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE